



CHANGE-KIT-07

Access MAX 250, 300, 400 / TOMAHAWK 250, 300, 400

COMPLETE OIL CHANGE KIT – INSTRUCTIONS

Engine oil change:

- Place the ATV on a level surface and secure it against rolling away.
- Select Neutral, start the engine, let it warm up on idle for cca 5 minutes and turn the engine off.
- Place a suitable container / pan that holds at least 3.0 liters under the engine.
- Loosen the drain plug with magnet at the bottom of the engine (17mm Hex Screw). Do not drop the screw into the pan.
- Carefully drain warm oil and allow it to drain completely. **WARNING: OIL CAN BE VERY HOT!**
- Wipe away any spilled oil.
- Loosen the drain plug with strainer.
- Clean the strainer.
- Screw the drain plug with magnet and drain plug with strainer back in. (Tightening torque: 30 Nm).
- Unscrew and remove the oil filling plug.
- Using a funnel, carefully pour about 1,8 liters of 10W-40 oil into the engine. Avoid overfilling the funnel.
- When the oil level reaches about halfway through the oil window on the side of the engine, screw the filler plug back in.
- Start the engine, check for oil leaks.
- After cca. 1 minute stop the engine, wait for about 10 seconds, and check the oil level.
- If the level is not about halfway through the oil window, add oil to the correct level by repeating the steps above.
- Once the oil level is correct, screw the filler plug back in and wipe off any remaining oil residues.
- Congratulations: you have successfully replaced your oil!
- Dispose of the used oil ecologically - take your used oil in for recycling.

Transmission Oil Change:

- Place the ATV on a level surface and secure it against moving.
- Place a suitable pan under the gearbox (behind the engine) to collect the drained oil.
- Remove the **17mm** oil drain plug and its washer and drain the oil from the transmission case.
NOTE: Do not loosen the smaller 14mm screw ! (This is the Gear Shift Drum locking screw).
- Check the oil drain plug gasket for damage and replace it if necessary.
- Install the drain plug with the washer and tighten it to 33 Nm.
- Unscrew the white plastic filler plug and pour 0.7 litres of Maxima HYPOID GEAR LUBE PREMIUM 80W90 into the transmission.
- Screw the white filler plug back in, wipe off any residual oil and check for oil leaks from the gearbox.
- Your oil change is now completed. Dispose of the used oil ecologically - take your used oil in for recycling.

CHANGE-KIT-07 includes:

- **2x 1L MAXIMA ATV PREMIUM 10W40 4T Oil**, Part: 33901 (Engine oil)
- **1L MAXIMA PREMIUM GEAR OIL 80W90 Oil**, Part: 43901 (for Transmission)
- **Instruction sheet**



OFFICIAL DISTRIBUTOR:

ASP Group Distributing, Staroplzenecka 290, 326 00, Letkov, CZ, tel: +420 378 21 21 21, info@aspgroup.cz, www.aspgroup.eu