



CHANGE-KIT-30

LINHAI M565L, M570L, Promax 570/650, T-Boss 570

ENGINE OIL AND OIL FILTER REPLACEMENT INSTRUCTIONS

- Place the ATV on a level surface.
- Start the engine, let it warm up and turn the engine off.
- Engage the Parking brake.
- Place a suitable container / pan that holds at least 3 liters under the engine.
- Loosen the drain plug at the bottom of the engine (17mm Hex Screw). Do not drop the screw into the pan.
- Carefully drain warm oil and allow it to drain completely. **WARNING: OIL CAN BE VERY HOT!**
- Loosen the oil filter cartridge with the oil filter wrench. The oil filter is located in front of the engine.
- Allow the oil to drain from the oil filter cartridge.
- Wipe away any spilled oil.
- Lubricate the rubber gasket of a new oil filter with clean engine oil.
- Install new oil filter cartridge.
 - Screw the filter on the engine hand-tight. Do not over tighten the filter.
- Screw the oil drain plug back into the engine. (Tightening torque: 30 Nm).
- Unscrew and remove the oil dip stick - new oil filling point.
- Using a funnel, carefully pour about 2.7 liters of 10W-40 oil into the engine. Avoid overfilling the funnel.
- Put the dip stick on top of the threads (do not screw it in), pull the dip stick out and check the oil level.
- If the oil level is low, top up the oil.
- If the oil level reaches the upper mark on the dip stick, reinstall the dip stick.
- In general, you should use about 2.8-3 liters of oil when changing.
- Clean spilled oil, start the engine and check for oil leaks.
- After cca 1 minute stop the engine, wait for about 10 seconds, unscrew the oil dip stick again and wipe it with a clean rag. Put the dip stick on top of the threads (do not screw it in), pull the dip stick out and check the oil level.
- The oil level should be between the upper and lower marks.
- If not, add the oil to the correct level by repeating the steps above.
- Once the oil level is correct, screw the dip stick back into the engine and wipe off any oil residues. Congratulations: you have successfully replaced your oil and oil filter!
- Dispose of the used oil ecologically - take your used oil and oil filter in for recycling.

CHANGE-KIT-30 includes:

- **3x 1L MAXIMA ATV PREMIUM 10W40 4T Motor Oil**, Code: 33901
- **1x OIL FILTER**, Code: 38091
- **Instruction sheet**