

Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

1.1 Product Identifier

Trade Name: SC1
Product Number: 78920

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Product Use: High gloss coating - aerosol

Restrictions on Use: None known

1.3 Details of the Supplier of the Safety Data Sheet

Manufacturer: Maxima Racing Oils

9266 Abraham Way Santee, CA 92071

USA

Information Phone Number: +1 619 449 5000

E-mail: info@maximausa.com

1.4 Emergency Telephone Number

Emergency Spill Information: CHEMTREC +1 703 527 3887 (24 hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

CLP (1272/2008) Classification:

Aerosol 1 (H222, H229)

Aspiration Toxicity Category 1 (H304)

Skin Irritation Category 2 (H315)

Specific Target Organ Toxicity Single Exposure Category 3 (H336)

2.2 Label Elements

Danger





Released: 2015-05-28

SC1

Version: 1.0 Revision Date: 2019-02-11

Hazard Statements	Precautionary Phrases
H222 Extremely flammable aerosol	P210 Keep away from heat, hot surfaces, sparks,
H229 Pressurised container: May burst if heated	open flames and other ignition sources. No
H315 Causes skin irritation	smoking.
H336 May cause drowsiness or dizziness	P211 Do not spray on an open flame or other
	ignition source.
	P251 Do not pierce or burn, even after use.
	P410 + P412 Protect from sunlight. Do not
	expose to temperatures exceeding 50°C.
	P261 Avoid breathing dust/fume/
	gas/mist/vapours/spray.
	P264 Wash hands and arms thoroughly after
	handling.
	P271 Use only outdoors or in a well-ventilated
	area.
	P280 Wear protective gloves.
	P302 + P352 IF ON SKIN: Wash with soap and
	water.
	P304 + P340 IF INHALED: Remove person to fresh
	air and keep comfortable for breathing.
	P332 + P313 If skin irritation occurs: Get medical
	attention.
	P362 + P364 Take off contaminated clothing and
	wash it before reuse.
	P405 Store locked up.
	P501 Dispose of contents and container in
	accordance with local and national regulations.

EUH Statements

EUH208 (Contains orange terpenes. May produce an allergic reaction.)

2.3 Other Hazards: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixture

Chemical Name	CAS#	EINECS#	REACH	CLP Classification	% w/w
			registration#		
Naphtha (petroleum),	64741-66-8	921-728-3	-	Flammable Liquids 2 (H225)	40-60
light alkylate				Aspiration Toxicity 1 (H304)	



Released: 2015-05-28

SC₁

Version: 1.0 Revision Date: 2019-02-11

Neieaseu. 2015-05	20			Nevision Date. 20	013 02 11
				Skin Irritation 2 (H315)	
				Specific Target Organ	
				Toxicity Single	
				Exposure 3 (H336)	
Petroleum	68476-86-8	270-705-8	-	Flammable Gases 1	30-50
gases, liquefied,				(H220)	
sweetened ^K				Gas under pressure,	
				Liquefied Gas (H280)	
Polydimethyl-	63148-62-9	613-156-5	-	NC	5-15
siloxane					
Orange	-	-	-	Flammable Liquids 3	0.1-
terpenes				(H226)	<0.15
				Aspiration Toxicity 1	
				(H304)	
				Skin Irritation 2 (H315)	
				Skin Sensitisation 1	
				(H317)	

Note K. The substance contains less than 0.1% w/w 1,3-butadiene (EC 203-450-8), and does not need to be classified as a carcinogen or mutagen.

The exact percentage and composition are being withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

4.1 Description of First Aid Measures

Eye: Flush eyes with water for several minutes. Remove contact lenses, if present and easy to do so. If eye irritation persists, get medical attention.

Skin: Wash skin with soap and water. Remove clothing and shoes if contaminated. Launder clothing before reuse. If irritation or rash develops, get medical attention.

Inhalation: If inhaled remove to fresh air. If irritation or difficulty in breathing occurs, get medical attention.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

- **4.2 Most Important symptoms and effects, both acute and delayed:** May cause mild, short-lasting discomfort to eyes. Causes skin irritation. The product contains small amounts of a sensitiser, may cause dermatitis in sensitive individuals. Inhalation of vapours or mist may cause central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting may cause lung damage.
- **4.3 Indication of any immediate medical attention and special treatment needed:** As a general rule, and in all cases of doubt or when symptoms persist, always seek medical attention. Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET





SC₁

Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

SECTION 5: FIRE AND EXPLOSION DATA

5.1 Extinguishing Media: Use alcohol-resistant foam, dry chemical or carbon dioxide (CO2) to extinguish flames. Water may be ineffective but can be used to cool exposed containers and structures and disperse flammable vapours.

5.2 Special Hazards Arising from the Substance or Mixture

Unusual Fire and Explosion Hazards: Contents under pressure. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 50°C may cause cans to burst.

Combustion Products: Combustion will produce carbon oxides and unidentified organic compounds.

5.3 Advice for Fire-Fighters:

Special Fire Fighting Procedures: Firefighters should wear full emergency equipment and an approved positive pressure self-contained breathing apparatus. Cool exposed intact containers with water. Protect against bursting cans.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Evacuate spill area and keep unprotected personnel away. Remove all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective equipment. Wash thoroughly after handling. See also: "Personal Protection "section 8.

6.2 Environmental Precautions:

Avoid release into the environment. Report spill as required by local and national regulations.

6.3 Methods and Material for Containment and Cleaning Up:

Contain and collect using inert absorbent materials and place in appropriate containers for disposal. Use non-sparking tools and equipment. If spill has not ignited, use water spray to disperse the vapours and protect personnel attempting to stop leak. Ensure collected material is handled in accordance with section 13 "Disposal Considerations".

6.4 Reference to Other Sections: Refer to Section 8 for personal protective equipment and Section 13 for disposal information.

SAFETY DATA SHEET





SC₁

Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapours and mists. Wear protective clothing and equipment. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep away from heat, sparks, flames and all other sources of ignition. Contents under pressure. Do not permit smoking in use or storage areas. Do not expose to temperatures above 50°C. Do not puncture or incinerate containers.

- **7.2 Conditions for Safe Storage, Including any Incompatibilities**: Store in a cool, dry, well-ventilated area away from heat, direct sunlight and all sources of ignition. Store in accordance with regulations for the storage of aerosol containers. Store away from oxidisers and other incompatible materials. Protect from physical damage.
- **7.3 Specific end use(s):** The product is to be used as a high gloss coating. Contact with the skin should be prevented due to the risk of irritation. If inhalation of high concentrations of vapours and mists cannot be prevented appropriate personal protective equipment should be used.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters: Refer to country-specific legislation for specific requirements where not listed below.

Chemical Name	Exposure Limits		
Naphtha (petroleum), light alkylate	241 ppm (1200 mg/m³) TWA Manufacturer		
Petroleum gases, liquefied, sweetened	None Established		
Polydimethylsiloxane	None Established		
Orange terpenes	None Established		

8.2 Exposure Controls:

Appropriate Engineering Controls: Use with adequate local exhaust ventilation to minimise exposure. Use explosion proof equipment where required.

Respiratory Protection: If the exposure is excessive or irritation is experienced, an approved particulate/organic vapour respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with local regulations and good industrial hygiene practice.

Skin Protection: Wear impervious gloves in accordance with EN 374 to avoid skin contact. Protective clothing if needed to avoid skin contact and contamination of personal clothing. Suitable washing should be available in the work area. Contaminated clothing should be removed and laundered before re-use.

Eye Protection: Wear chemical goggles in accordance with EN 166 to prevent eye contact. **Other Protective Equipment:** None should be needed under normal use conditions. In Europe follow EN 13034.





Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic Physical and Chemical Properties

Appearance Liquid in an aerosol container

Colour Clear

Odour Pleasant odour Odour Threshold No data available рН No data available Freezing Point No data available **Boiling Point** 115°C (concentrate) Flash Point 7°C (concentrate) No data available **Evaporation Rate** Flammable aerosol Flammability (solid, gas) **Upper Explosion Limit** Not established Lower Explosion Limit 1.8% (propellant) Vapour Pressure No data available Vapour Density (Air=1) No data available No data available **Relative Density** Solubility No data available

Partition Coefficient: n-octanol/water

icient: n- No data available

No data available

Auto Ignition Temperature

Decomposition No data available

Temperature

Volatile Organic No data available

Compounds (VOC)

Viscosity < 20.5 cSt @ 40°C (concentrate)

9.2 Other Information: None available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Not expected to be reactive

10.2 Chemical Stability: Stable

10.3 Possibility of Hazardous Reactions: Vapours may form explosive mixture with air.

10.4 Conditions to Avoid: Keep away from heat, sparks, flames and all other sources of ignition. Dropping containers may cause bursting.

10.5 Incompatible Materials: Avoid contact with strong oxidising agents.

6 of 10





Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

10.6 Hazardous Decomposition Products: Thermal decomposition may produce carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects:

Potential Health Effects:

Eye Contact: May cause mild, short-lasting discomfort to eyes.

Skin Contact: Causes skin irritation with non-allergic dermatitis. May cause allergic dermatitis in sensitive individuals.

Inhalation: Inhalation of vapours or mist may cause central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness.

Ingestion: Swallowing large amounts may cause gastrointestinal effects including nausea and diarrhoea. Aspiration during swallowing or vomiting may cause lung damage.

Chronic Effects of Overexposure: Used motor oils have been found to cause skin cancer in skin painting studies with laboratory animals.

Acute Toxicity Values:

Naphtha (petroleum), light alkylate: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >20 mg/L/4 h (vapour), Dermal rat LD50 >2000 mg/kg

Polydimethylsiloxane: Oral rat LD50 >15,400 mg/kg, Inhalation rat LC50 NA, Dermal rabbit LD50 > 2000 mg/kg

Skin corrosion/irritation: Product is classified as a skin irritant.

Eye damage/irritation: The product does not meet the criteria to be classified as an eye irritant.

Respiratory Irritation: The product does not contain any components that are respiratory irritants.

Respiratory Sensitisation: The product does not contain any components that are respiratory sensitisers.

Skin Sensitisation: The product contains small amounts of a skin sensitiser. May cause allergic dermatitis in sensitive individuals.

Germ Cell Mutagenicity: The product does not contain any components that are germ cell mutagens.

Carcinogenicity: None of the components of this product present at 0.1% or greater are listed as carcinogens by IARC, NTP or the EU CLP.

Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects.



Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

Specific Target Organ Toxicity:

Single Exposure: The product is classified as a specific target organ toxicant, single exposure,

category 3 with narcotic effects.

Repeat Exposure: No data available

Aspiration Hazard: This product does meet the criteria of an aspiration hazard as the kinematic viscosity is below 20.5 cSt @ 40°C. Product is not labelled as an aspiration hazard due to packaging as an aerosol.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Naphtha (petroleum), light alkylate: 96 h LL50 Oncorhynchus mykiss 18.4 mg/L, 48 h EL50 Daphnia magna 2.4 mg/L, 72 h EL50 Pseudokircherinella subcapitata 29 mg/l.

Polydimethylsiloxane: LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested.

12.2 Persistence and Degradability

Naphtha (petroleum), light alkylate is inherently biodegradable (22% degraded after 28 days). Polydimethylsiloxane: not biodegradable.

12.3 Bioaccumulative Potential

Naphtha (petroleum), light alkylate has the potential to bioaccumulate.

Polydimethylsiloxane: no bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

12.4 Mobility in Soil

Naphtha (petroleum), light alkylate: highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Polydimethylsiloxane: expected to be relatively immobile in soil (Koc > 5000).

12.5 Results of PBT and vPvB Assessment: Components do not meet the criteria of PBT or vPvB.

12.6 Other Adverse Effects: None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods:

Dispose in accordance with all local and national regulations.

SECTION 14: TRANSPORTATION INFORMATION

14.1 UN	14.2 UN Proper	14.3	14.4	14.5
Number	Shipping Name	Hazard	Packing	Environmental
		Class(s)	Group	Hazards



Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

EU ADR/RID	1950	Aerosols, flammable	2.1 (5F)	-	Yes
IMDG	1950	Aerosols	2.1	-	Yes
IATA/ICAO	1950	Aerosols	2.1	-	Yes

14.6 Special Precautions for User: Not applicable

14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code: Not applicable – product is transported only in packaged form

SECTION 15: REGULATORY INFORMATION

15.1 Safety, Health and Environment Regulations/Legislation Specific for the Substance or Mixture:

This SDS conforms to Regulation (EU) No. 1907/2006 and 2015/830. Label in accordance with Regulation (EC) No. 1272/2008 (CLP).

SECTION 16: OTHER INFORMATION

Supersedes: 28 May, 2018

Date Updated: 11 February, 2019 **Revision Summary:** All sections revised.

CLP Classification for Reference (See Sections 2 and 3):

Flam. Gas. 1 Flammable Gases Category 1

Aerosol 1 Aerosol Category 1

Flam. Liq. 2 Flammable Liquids Category 2 Flam. Liq. 3 Flammable Liquids Category 3

Gas under pressure: Liquefied gas

Asp. Tox. 1 Aspiration Toxicity Category 1 Skin Irrit. 2 Skin Irritation Category 2 Skin Sens. 1 Skin Sensitisation Category 1

STOT SE 3 Specific Target Organ Toxicity Single Exposure Category 3

H220 Extremely flammable gas

H222 Extremely flammable aerosol

H225 Highly flammable liquid and vapour

H226 Flammable liquid and vapour

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H336 May cause drowsiness or dizziness

SAFETY DATA SHEET





SC₁

Version: 1.0

Released: 2015-05-28 Revision Date: 2019-02-11

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.